SECTION 1 - PRODUCT IDENTIFICATION

Product identifier/Trade name: WYTE GREASE
Product code/Internal Identification: 11397
Product use/Description: Water resistant lubricant. 290 g aerosol container.
Product chemical name: N/Ap
Chemical family: Mixture of hydrocarbons and propellant.
MSDS preparation/review date: February 01, 2012
Supplier identifier: Asalco Inc.
44, ch. Des Ursulines, Stanstead, Québec (Canada), J0B 3E0
Telephone 819-876-2211; Fax 819-876-5373; Internet www.asalco.com
Manufacturer identifier: Same as supplier
Emergency phone number: (613) 996-6666 (CANUTEC)
WHMIS Classification: A – Compressed gas
B5 – Flammable aerosol
D2B – Toxic material with other toxic effects

SECTION 2 - CHEMICAL COMPOSITION / HAZARDOUS INGREDIENTS

Hazardous Ingredients	CAS #	% (weight)	LD_{50} (route, species)	LC_{50} (species)
Light aliphatic solvent naphtha	64742-89-8	30 – 60	N/Av	N/Av
Naphtha (petroleum), heavy alkylate	64741-65-7	5 - 10	N/Av	N/Av
Isobutane	75-28-5	5-10	N/Ap	658000 mg/m^3 4 hrs (rat)
Propane	74-98-6	10-30	N/Ap	N/Av

SECTION 3 - HAZARDS IDENTIFICATION

Emergency Overview

DANGER! Flammable aerosol. Contents under pressure. May cause skin and eye irritation. May cause headache, nausea, dizziness and other central nervous system effects.

POTENTIAL HEALTH EFFECTS

Primary entry route(s): Skin contact, eye contact, ingestion and inhalation.

Effects of short-term (acute) exposure:

Inhalation:

May cause irritation to the nose, throat and respiratory tract, and central nervous system depression. Symptoms may include headache, nausea, vomiting, loss of coordination and other central nervous system effects. In extremely high concentrations, product may act as an asphyxiant and cause increased breathing and pulse rates, fatigue, nausea, vomiting and unconsciousness.

Skin:

Direct skin contact may cause mild irritation. If sprayed directly onto the skin, symptoms of frostbite may be experienced including numbness, prickling and itching.

Eye:

Direct eye contact may cause mild irritation. Symptoms may include redness, stinging, tearing and pain. If product is sprayed directly into the eyes, contact could cause freezing of the eye.

Ingestion:

If the product is sprayed directly into mouth, it may cause irritation to the mouth, throat and stomach. Symptoms may include dizziness, drowsiness, nausea, headache and other central nervous system effects. Product may present an aspiration hazard, and cause life-threatening lung injury following ingestion.

Effects of long-term (chronic) exposure:

Prolonged or repeated contact may cause drying, cracking and defatting of the skin (dermatitis).

Other important hazards:

Refer to Section 11, Toxicological Information, for further information.

SECTION 4 - FIRST AID MEASURES

Inhalation:

Remove source of contamination or have victim move to fresh air. If not breathing, give artificial respiration. Obtain medical attention immediately.

Skin contact:

Flush contaminated area with lukewarm, gently running water for at least 20 minutes. If irritation persists, obtain medical advice.

Eye contact:

Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for at least 20 minutes. Obtain medical attention immediately.

Ingestion:

NEVER give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Rinse mouth thoroughly with water. DO NOT INDUCE VOMITING. Have victim drink two glasses of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Repeat administration of water. Obtain medical attention immediately.

SECTION 5 - FIRE FIGHTING MEASURES

Fire hazards/conditions of flammability:

FLAMMABLE AEROSOL. Material will ignite when exposed to sources of high heat or flame. Flame projection is > 15 cm but < 100 cm and no flashback observed.

Flash point (Method): N/Av

Lower flammable limit (% by volume): 1

Upper flammable limit (% by volume): 9.5

Sensitivity to mechanical impact: Aerosols may explode or become projectiles after a mechanical impact.

Sensitivity to static discharge:

This material may be sensitive to static discharge when vapours are present between the lower and upper flammable limits.

Auto-ignition temperature: 245-365°C

Suitable extinguishing media:

Carbon dioxide, dry chemical powder and appropriate foam. Do not use water jet, as this may spread and scatter burning material.

Special fire-fighting procedures/equipment:

During a fire, irritating/toxic smoke and fumes may be generated. Do not enter fire area without proper protection. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full facepiece. Shield personnel to protect from venting, rupturing or bursting cans. Move containers from fire area if it can be done without risk. Water spray may be useful in cooling equipment and cans exposed to heat and flame.

Hazardous combustion products: Carbon oxides, sulfur oxides and other irritating fumes and smoke.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions:

Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with clean-up should wear the appropriate protective equipment (See Section 8).

Spill response/Cleanup:

Ventilate area of release. Eliminate all sources of ignition. Remove or isolate flammable and combustible materials. Stop the leak if it can be done safely. Use only non-sparking tools during the clean-up process. Contain and absorb any spilled liquid concentrate with inert absorbent material, then place material into a container for later disposal (see Section 13). Do not use combustible absorbent material, such as sawdust. Contaminated absorbent material may pose the same hazards as the spilled product. Notify the appropriate authorities as required.

Environmental precautions:

Confine spill, preventing it from entering sewer lines or waterways. Dispose of as per local, state and federal regulations.

SECTION 7 - HANDLING AND STORAGE

Safe handling procedures:

Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Do not use near welding operations, flames or hot surfaces. Handling equipment should be properly grounded. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing vapours or mists. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Do not puncture or incinerate containers. Avoid generating high concentrations of vapours or mists. Keep away from incompatibles such as strong oxidizing materials. Keep containers closed when not in use. Empty containers are always dangerous. Assume that empty containers contain residues which are hazardous.

Storage requirements:

Store in a cool (< 50°C), well-ventilated area, away from heat and ignition sources. Store away from incompatible materials. Inspect all incoming containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of obstruction and accessible only to trained personnel. Inspect periodically for damage or leaks.

Incompatible materials:

STRONG OXIDIZING MATERIALS.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure limits: There is no available data for the product. See below for individual ingredient exposure limits.

Ingredient	OSHA PEL		ACGIH TLV	
	TWA	STEL	TWA	STEL
Light aliphatic solvent naphtha	N/Av	N/Av	N/Av	N/Av
Naphtha (petroleum), heavy alkylate	N/Av	N/Av	N/Av	N/Av
Isobutane	N/Av	N/Av	1000 ppm	N/Av
Propane	1000 ppm	N/Av	1000 ppm	N/Av

Engineering controls:

Use under well-ventilated conditions. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure limits.

Respiratory Protection:

Respiratory protection is required if the concentrations are higher than the exposure limits. Use a NIOSH approved respirators if the exposure limits are unknown.

Protective Clothing/Equipment:

Chemically protective gloves (impervious), and other protective clothing to prevent prolonged or repeated skin contact, should be worn during all handling operations. Wear protective chemical splash goggles to prevent mists from entering the eyes. Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

General Hygiene Considerations:

Avoid generating high concentrations of vapours or mists. Avoid contact with skin and eyes. Avoid breathing vapours or mists. Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material. Remove and wash contaminated work clothing before re-use.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical state, colour and odour: Off white, aerosolized liquid. Slight petroleum odour.

Odour threshold: N/Av

pH : N/Av

Melting/freezing point: N/Av

Coefficient of oil/water distribution: N/Av

Specific gravity or density (water = 1): 0.74-0.78

Evaporation rate (n-Butyl acetate = 1): < 1

Boiling point: 90-205 °C

Vapour pressure (@ 20°C): 65-75 psig

Solubility in water: Negligible

Vapour density (Air = 1): > 1 heavier than air

% volatile by volume: N/Av

SECTION 10 - REACTIVITY AND STABILITY DATA

Stability and reactivity:
Stable under the recommended storage and handling conditions prescribed.
Polymerization:
Hazardous polymerization will not occur.
Conditions to avoid:
Avoid heat, sparks, direct flame and other ignition sources. Avoid direct sunlight.
Materials to avoid:
Incompatible materials (see Section 7).
Hazardous decomposition products:
None known. Refer to 'Hazardous combustion products', Section 5.

SECTION 11 - TOXICOLOGICAL INFORMATION

Toxicological data:
There is no available data for the product itself, only for the ingredients. **For more details, refer to Section 2.**
Carcinogenicity: No ingredient listed by IARC, ACGIH, NTP or OSHA as a carcinogen.
Teratogenicity, mutagenicity, other reproductive effects: N/Av
Skin sensitization: None known.
Respiratory tract sensitization: None known
Conditions aggravated by exposure: None known
Synergistic materials: N/Av

SECTION 12 - ECOLOGICAL INFORMATION

Environmental effects: There is no available data on the product itself. The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.
Important environmental characteristics: N/Av
Aquatic toxicity: N/Av

SECTION 13 - WASTE DISPOSAL

Handling and storage conditions for disposal:
Store material for disposal as indicated in Handling and Storage (Section 7). Do not puncture or incinerate empty spray cans.
Methods of disposal:
Review federal, provincial and local government requirements prior to disposal.

SECTION 14 - TRANSPORTATION INFORMATION

Transportation of Dangerous Goods Regulations (TDGR) :
TDG Classification: AEROSOL; Class 2.1; UN1950
Special case: Product can also be shipped as a LIMITED QUANTITY/CONSUMER COMMODITY according to TDG Section 1.17.

SECTION 15 - REGULATORY INFORMATION

WHMIS information:

Product is regulated according to the Controlled Product Regulations (CPR) in Canada. Refer to Section 1 for the appropriate WHMIS classification.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and this MSDS contains all the information required by the CPR.

Canadian Environmental Protection Act (CEPA) information:

The ingredients in this product are listed on the DSL.

United States TSCA information:

The ingredients in this product are listed on the TSCA.

Hazardous Materials Identification System (HMIS):

HEALTH: 2 FLAMMABILITY: 4 REACTIVITY: 1 PERSONAL PROTECTION: See Section 8.
HAZARD SCALE: * = Chronic hazard 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

National Fire Protection Association (NFPA):

HEALTH: 2 FLAMMABILITY: 4 INSTABILITY: 0 SPECIAL HAZARDS: None.
HAZARD SCALE: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

SECTION 16 - OTHER INFORMATION

Prepared by: NSS ENTREPRISE INC. for Asalco Inc.
Telephone number: Telephone 819-876-2211 Fax 819-876-5373 Internet www.asalco.com

References:

1. Material Safety Data Sheets from manufacturer/supplier.
2. CSST, Répertoire Toxicologique, Les produits, 2012.
3. Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2012.

Abbreviations:

ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstract Service
DSL	Domestic Substance List
IARC	International Agency for Research on Cancer
LC	Lethal concentration
LD	Lethal Dosage
N/Ap	Not applicable
N/Av	Not available
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program (U.S.A.)
OSHA	Occupational Safety and Health Administration (U.S.A.)
PEL	Permissible Exposure Limit
STEL	Short-term Exposure Limit
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
TWA	Time Weighted Average
WHMIS	Workplace Hazardous Materials Information System

End of the MSDS